

## Generator LED 20W – White

### Range

LUXERI light source range offers a guarantee of professional quality for all of your lighting projects based on optical fiber. Size makes them easy to handle lighting effects discreetly. Each generator is recognized by its performance.

### Definition

**Generator LED 20W – white** is used to achieve starry ceilings, projects of lighting. This generator is equipped with LED COB. It is available in many temperature of color.

Its luminous intensity can be adjusted by means of an integrated potentiometer. It can be remotely controlled by 0-10V signal.



### Technical features

DATA	GLE1120BLA-A
Light source	LED COB
Dimming	Manual dimming or 0 – 10V
Color temperature	2700°K :1470lm, IRC 90 - 3000°K : 1795lm, IRC90 - 3500°K : 1850lm, IRC 90 – 4000°K : 1850 lm, IRC90 – 6500°K : 2300lm, IRC90
Maximum number of fibers	300 – Ø 1 mm
Life span	50 000 H
Power consumption	20W
Supply voltage	190-240X AC 50HZ
Casing	143 x 110 x 131mm
Weight	1,35 kg
Operating temperature	+5°C < Ta < +40°C
Photometry	292 lux at 50cm With a branch of 20 FOP Ø 1 mm

LUXERI is specialized for more than 20 years in the sale of products with plastic fiber used in data transmission and in lighting. From the study of complex projects to the sale of quality products thanks to TORAY® fiber, LUXERI offers a wide range of products and services aimed at professionals and companies.