

FIXED

Range

By providing wide range of end fittings with fibre optic harnesses, LUXERI offers a guarantee of professional quality for all of your lighting projects.


Discreet, esthetically pleasing, they enable focusing and / or directing the light.

Definition

« FIXED » end fitting is rooted, made up of polished lens. Thanks to its lens, it allows better focalization of light beam on given object

This end fitting exists with various finishing touches:

BLACK: SPF50AL20P0N
WHITE: SPF50AL20P0B
GOLDEN: SPF50AL20P0D
CHROME: SPF50AL20P0C
ANODIZED: SPF50AL20P02
INOX 316L: SPF50AL20P20



Technical features

DATA	SPF50AL10PXX
Focalization (°)	From 14 to 18
Hole diameter (mm)	40
End ferrule	M10x100
Miscellaneous	Integrated with a system of springs
Photometry	2200 lux (18°) and 4900 lux (14°) at 50 cm With a generator 150 W HQI and a branch of 20 FOP Ø 1 mm
Dimensions	Fixed end fitting Ø 50 mm

Remarks:

Leave free gap of 90mm behind the end fitting in order to set optical fiber Integrated in dividing wall of10mm at maximum

LUXERI Is specialized for more than 20 years in the sale of products with plastic fiber used in data transmission an in lighting. From the study of complex projects to the sale of quality products thanks to TORAY® fiber, **LUXERI** offers a wide range of products and services aimed at professionals and companies.